

C-Profile Type 2986

C-profile, slot width 18 mm, to DIN EN 60715, with combi perforation

2986/2 FKL


EAN Code: 4013339923243

Smallest packaging unit:2 m

quantity unit:m M



the photorealistic images are to be considered as reference images



Article Description

C-profile, C-profile, slot width 18 mm,40x22x2000mm, combi perforation, steel, hot dip galvanised DIN EN ISO 1461

Weight

Weight per quantity unit	1,645 kg/ m
Weight in kg per 100	164 kg/ 100m

Physical Article Dimensions

Height	22.00 mm
Width	40.00 mm
Depth/length	2000 mm

Technical Datasheet

Niedax rails

2986/2 FKL

the photorealistic images are to be considered as reference images

Additional Price Information

Article group	N13
quantity unit	m

Packing Dimension

2 meters = 1 piece		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	2000 mm	Width	40.00 mm	Height	22.00 mm
Gross weight	3,29 kg	Volume	0,002 m³		
Min. quantity	2.00 m	Max. Quantity	2.00 m		

550 meters = 1 rack					
Lenght	2000 mm	Width	850 mm	Height	770 mm
Gross weight	963 kg	Volume	1,309 m³		
Min. Quantity	550.00 m	Max. Quantity	550.00 m		

Tender Text

C-profile model 2986 to DIN EN 60715, with combination holes. Suitable U-clamps (BU... and BUK...). The protective cap SKC 86 must be fitted in personal hazard areas. To ensure that the protective cap can be fitted without problems, a distance of at least 30 mm from the end of the profile must be maintained.

Dimensions (approx. dimensions)

Height H x width W x material thickness t : 22 x 40 x 2 mm

Slot width : 18 mm

Profile perforation : 9 x 16 mm and Ø 11 mm

central distance : 25 mm

Delivery length L : 2000 mm

Material : steel, hot-dip galvanised acc. to DIN EN ISO 1461

NIEDAX Model No. : 2986/2 FKL

EP material_____ EP wage_____

Unit price/meter

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098