

C-Profile Type 2986


C-profile, slot width 18 mm, acc. to DIN EN 60715, perforated

2986/700 SL

EAN Code: 4013339899678

Smallest packaging unit:1 pc.

the photorealistic images are to be considered as reference images



Article Description

C-profile, C-profile, slot width 18 mm, 40x22x700 mm, perforated, steel, pre-galvanised according to DIN EN 10346

Weight

Weight per quantity unit	1,044 kg/ pcs.
Weight in kg per 100	104 kg/ 100pcs.

Physical Article Dimensions

Height	22.00 mm
Width	40.00 mm
Depth/length	700 mm

Technical Datasheet

Niedax rails

2986/700 SL

the photorealistic images are to be considered as reference images

Additional Price Information

Article group	N13
quantity unit	pcs.

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	700 mm	Width	40.00 mm	Height	22.00 mm
Gross weight	1,04 kg	Volume	0,001 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

C-profile model 2986 to DIN EN 60715, perforated.
Suitable U-clamps (BU... and BUK...).

The protective cap SKC 86 must be fitted in personal hazard areas. To ensure that the protective cap can be fitted without problems, a distance of at least 30 mm from the end of the profile must be maintained.

Dimensions (approx. dimensions)
Height H x width W x material thickness t : 22 x 40 x 2 mm
Slot width : 18 mm
Profile perforation : 11.5 x 30 mm
central distance : 50 mm
Delivery length L : 700 mm
Material : steel, pre-galvanised acc. to DIN EN 10346
NIEDAX Model No. : 2986/700 SL
EP Material_____ EP Wage_____
Unit price/piece

Safety & Environment

REACH Date	21.01.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098