

Technical Datasheet

Vertical Cable Ladder System



Vertical Cable Ladder

made of U 6040 profiles and C-profiles 2986, unassembled

STUC 60/1105 F



EAN Code: 4013339924783

Smallest packaging unit: 4,5 m

quantity unit: m M



the photorealistic images are to be considered as reference images



Article Description

Vertical cable ladder, 60x1115x4500 mm, rung distance 500 mm, steel, hot dip galvanised DIN EN ISO 1461, unmounted

Incl. accessories

4,5 meter = 1 piece		✓ lowest delivery unit	✓ preferred delivery unit
Model No.	Description	quantity	
FLM 8X16 F	Mushroom-head bolt M8, similar DIN 603, length 16 mm, steel, hot dip galvanised DIN EN ISO 1461	18 pcs.	
UGM 8 F	Body washer aac. to DIN EN ISO 7093-1, outside-Ø 24 mm, steel, hot dip galvanised DIN EN ISO 1461	18 pcs.	

Additional Price Information

Article group	N13
quantity unit	m

Technical Datasheet

Vertical Cable Ladder System

STUC 60/1105 F

the photorealistic images are to be considered as reference images

Weight

Weight per quantity unit	10 kg/ m
Weight in kg per 100	1049 kg/ 100m

Physical Article Dimensions

Height	59.80 mm
Width	1115 mm
Depth/length	4500 mm

Packing Dimension

4,5 meters = 1 piece		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	4500 mm	Width	1115 mm	Height	60.00 mm
Gross weight	47 kg	Volume	0,300 m³		
Min. quantity	4.50 m	Max. Quantity	4.50 m		

Tender Text

Vertical cable ladder according to DIN EN 61537, consisting of 2 three-sided continuously perforated profiles U 6040 and screw-in C-profile rungs 2986 with 18 mm slot width, including hot-dip galvanised proportionate fixing accessories. The continuous perforation of the side rails allows the installation of additional rungs, for example alternating, for double-sided occupancy. For transport reasons, delivery is as a kit.

Corresponding U-clamps: BU... and BUK...

Delivery : unassembled

Dimensions (approx. dimensions)

Height H x width W : 60 x 1115 mm

Side rail dimensions : 40 x 60 x 40 mm

Material thickness side rail : 4 mm

Rung distance : 500 mm

Number of rails : 9 pieces

3-sided long rail perforation : 13 x 40 mm

Center distance : 50 mm

Combination perforation of rail : 9 x 16 mm and Ø 11 mm

Center distance : 25 mm

Load capacity at B/2 : 1 kN

Delivery length L : 4500 mm

Usable cross-section : 35190 mm²

Material : steel, hot-dip galvanised in accordance with DIN EN ISO 1461

NIEDAX Model No.: STUC 60/1105 F

EP Material_____ EP Wage_____

Unit price/metre

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Technical Datasheet

Vertical Cable Ladder System

STUC 60/1105 F

the photorealistic images are to be considered as reference images

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Barrier strip

Model No.	Description
KLWC 18 F	Barrier strip fastening clamp, for 18 mm slot width, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
RW 35 F	Barrier strip, 30x3000 mm, t=0,75 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Connector

Model No.	Description
VB 6040	Longitudinal connector for profile U 6040 and U 4530, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories