



Beam Connection Holder

with coupler

MIHK 3015 F

EAN Code: 4013339907120
Smallest packaging unit: 1 pc.

the photorealistic images are to be considered as reference images



Article Description

Beam connection holder, with coupling, Ø 30 mm, steel, hot dip galvanised DIN EN ISO 1461

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	863 g / pcs.
Weight in kg per 100	86 kg / 100pcs.

Physical Article Dimensions

Height	137.20 mm
Width	80.00 mm
Depth/length	120.00 mm

Technical Datasheet

Machine installation conduit

MIHK 3015 F

the photorealistic images are to be considered as reference images

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	120.00 mm	Width	80.00 mm	Height	138.00 mm
Gross weight	0,86 kg	Volume	0,001 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

Beam connection holder, with coupling, for crosswise fastening of cable protection conduits to the beams of cable trays and cable ladders.

Used for : machine installation conduit MI 30...

on cable trays RL..., RS... etc. and cable ladders KL...

Dimensions (approx. dimensions)

for beam clamping width W : ≤ 15 mm

Clamping length : 120 mm

Coupling Ø : 30 mm

Coupling length : 80 mm

Material : steel, hot-dip galvanised acc. to DIN EN ISO 1461

NIEDAX model no. : MIHK 3015 F

EP material_____ EP wage_____

Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73079210