

Beam Connection Holder



with coupler

MIHK 3015 E3

EAN Code: 4013339908325

Smallest packaging unit: 1 pc.

the photorealistic images are to be considered as reference images



Article Description

Beam connection holder, with coupling, Ø 30 mm, stainless steel, material code: 1.4301, AISI 304

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	793 g / pcs.
Weight in kg per 100	79 kg / 100pcs.

Physical Article Dimensions

Height	137.20 mm
Width	80.00 mm
Depth/length	120.00 mm

Technical Datasheet

Machine installation conduit

MIHK 3015 E3

the photorealistic images are to be considered as reference images

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	120.00 mm	Width	80.00 mm	Height	138.00 mm
Gross weight	0,79 kg	Volume	0,001 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

Beam connection holder, with coupling, for crosswise fastening of cable protection conduits to the beams of cable trays and cable ladders.

Used for : machine installation conduit MI 30...

on cable trays RL..., RS... etc. and cable ladder KL...

Dimensions (approx. dimensions)

for beam clamping width W : ≤ 15 mm

Clamping length : 120 mm

Coupling Ø : 30 mm

Coupling length : 80 mm

Material : stainless steel, material no. 1.4301, AISI 304

NIEDAX model no. : MIHK 3015 E3

EP material_____ EP wage_____

Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73072210