# **Technical Datasheet Supporting structure**



# Bracket/Overhead Hanger

## **TKS 450**

EAN Code: 4013339184606 Smallest packaging unit:10 pcs.











the photorealistic images are to be considered as reference images









## **Article Description**

Overhead hanger, 132x513 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories

# **Additional Price Information**

Article group	N13
quantity unit	pcs.

## Weight

Weight per quantity unit	757 g / pcs.
Weight in kg per 100	76 kg/100pcs.

## **Physical Article Dimensions**

Height	132.00 mm
Width	57.00 mm
Depth/length	513 mm

Aktualisiert am 21/8/2025 Page 1/2

# Technical Datasheet Supporting structure

**TKS 450** 

the photorealistic images are to be considered as reference images

## **Packing Dimension**

10 pieces = 1 carton		√ VP1-smallest packaging unit ( PU)  √ VP1-preferred PU			
Lenght	650 mm	Width	175.00 mm	Height	140.00 mm
Gross weight	8,2 kg	Volume	0,016 m³		
Min. quantity	10.00 pcs.	Max. Quantity	10.00 pcs.		

150 pieces = 1					
Lenght	750 mm	Width	750 mm	Height	730 mm
Gross weight	163 kg	Volume	0,411 m³		
Min. Quantity	150.00 pcs.	Max. Quantity	150.00 pcs.		

#### **Tender Text**

Overhead hanger, for mounting on horizontal ceilings, including proportional fastening accessories. For structural reasons, it is necessary to install the distance piece TKSD 20 when mounting on the ceiling in order to avoid deformation of the trapezoidal profile when tightening the fastening screw. Please order fastening screw SKM 10x25 to DIN EN ISO 4017 separately. The distance piece TKSD 20 is also required for hanging stem mounting with bracket on both sides. Please order fastening screw SKM 10x70 to DIN EN ISO 4017 separately. The load-bearing capacity data only apply if there is sufficient anchoring to the load-bearing substrate or if the installation on suspended standards is in accordance with regulations. In order to enable the protective cap to be fitted without any problems, the bracket must be fitted at a distance of X = 50 mm (lower edge of bracket - end of suspended support), above the end of the suspended support. Please observe additional regulations for use in functional maintenance! for brackets : TKS... ≤ 400 mm Dimensions (approx. dimensions) H x W x L : 132 x 57 x 513 mm Material: Steel, pre-galvanised acc. to DIN EN 10346 NIEDAX Model No. : TKS 450

NIEDAX Model No. : TKS 450
EP Material\_\_\_\_\_ EP Wage\_\_\_\_\_
Unit price/piece

## Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

#### **Origin & International Trade**

Country of origin	DE
Customs tarif number	73089059

Aktualisiert am 21/8/2025 Page 2 / 2