Technical Datasheet Supporting structure



Bracket/Overhead Hanger

TKS 600

EAN Code: 4013339184804 Smallest packaging unit:10 pcs.











the photorealistic images are to be considered as reference images









Article Description

Overhead hanger, 132x663 mm, steel, pre-galvanised according to DIN EN 10346, without accessories

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	944 g / pcs.
Weight in kg per 100	94 kg / 100pcs.

Physical Article Dimensions

Height	132.00 mm
Width	57.00 mm
Depth/length	663 mm

Aktualisiert am 21/8/2025 Page 1/2

Technical Datasheet Supporting structure

TKS 600

the photorealistic images are to be considered as reference images

Packing Dimension

10 pieces = 1 carton		√ VP1-smallest packaging unit (PU) √ VP1-preferred PU			
Lenght	730 mm	Width	200.00 mm	Height	150.00 mm
Gross weight	10 kg	Volume	0,022 m³		
Min. quantity	10.00 pcs.	Max. Quantity	10.00 pcs.		

300 pieces = 1 pallet					
Lenght	1200 mm	Width	800 mm	Height	1000 mm
Gross weight	324 kg	Volume	0,960 m³		
Min. Quantity	300.00 pcs.	Max. Quantity	300.00 pcs.		

Tender Text

Overhead hanger, for mounting on horizontal ceilings, including proportional fastening accessories. For structural reasons, it is necessary to install the distance piece TKSD 20 when mounting on the ceiling in order to avoid deformation of the trapezoidal profile when tightening the fastening screw. Please order fastening screw SKM 10x25 to DIN EN ISO 4017 separately. The distance piece TKSD 20 is also required for hanging stem mounting with bracket on both sides. Please order fastening screw SKM 10x70 to DIN EN ISO 4017 separately. The load-bearing capacity data only apply if there is sufficient anchoring to the load-bearing substrate or if the installation on suspended standards is in accordance with regulations. In order to enable the protective cap to be fitted without any problems, the bracket must be fitted at a distance of X = 50 mm (lower edge of bracket - end of suspended support), above the end of the suspended support. Please observe additional regulations for use in functional maintenance! for brackets : TKS... ≤ 400 mm Dimensions (approx. dimensions) H x W x L : 132 x 57 x 663 mm Material: Steel, pre-galvanised acc. to DIN EN 10346 NIEDAX Model No. : TKS 600

NIEDAX Model No.: TKS 600

EP Material _____ EP Wage _____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tarif number	73089059

Aktualisiert am 21/8/2025 Page 2 / 2