

Rungs for Vertical Cable Ladder



C-profile 2986 (40x22x2 mm)

SPCKL 86/400 F

EAN Code: 4013339924868

Smallest packaging unit: 1 pc.

the photorealistic images are to be considered as reference images



Article Description

Rungs, profile 2986, 40x22x400 mm, slot width 18 mm, perforated, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Incl. accessories

1 piece = 1 piece		✓ lowest delivery unit	– preferred delivery unit
Model No.	Description	quantity	
FLM 8X16 F	Mushroom-head bolt M8, similar DIN 603, length 16 mm, steel, hot dip galvanised DIN EN ISO 1461	2 pcs.	
UGM 8 F	Body washer aac. to DIN EN ISO 7093-1, outside-Ø 24 mm, steel, hot dip galvanised DIN EN ISO 1461	2 pcs.	

Additional Price Information

Article group	N13
quantity unit	pcs.

Technical Datasheet

Vertical Cable Ladder System

SPCKL 86/400 F

the photorealistic images are to be considered as reference images

Weight

Weight per quantity unit	709 g / pcs.
Weight in kg per 100	71 kg / 100pcs.

Physical Article Dimensions

Height	40.00 mm
Width	400 mm
Depth/length	22.00 mm

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	22.00 mm	Width	400 mm	Height	40.00 mm
Gross weight	0,71 kg	Volume	0,000 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

Rung, consisting of C-profile 2986 with combi-perforation and 18 mm slot width, including proportional fastening accessories in hot-dip galvanised. For additional requirements. Suitable U-clamps (BU... and BUK...).
for vertical cable ladder : STUC 60...
Dimensions (approx. dimensions)
Rung : 40 x 22 x 2 mm
Width W : 400 mm
Combination perforation : 9 x 16 mm and Ø 11 mm
Centre distance : 25 mm
Load capacity at B/2 : 1.75 kN
Material : Steel, hot-dip galvanised acc. to DIN EN ISO 1461
NIEDAX Model no. : SPCKL 86/400 F
EP Material_____ EP Wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tarif number	73269098