

Date

Electrical data

Ratings per IEC/EN 60664-1

| | |
|-----------------------------|---|
| Rated voltage (III/2) | 400 V |
| Rated surge voltage (III/2) | 4 kV |
| Rated current | 18 A |
| Legend (ratings) | (III / 2) ≙ Overvoltage category III / Pollution degree 2 |

Approvals per UL 1059

| | |
|---------------|---------|
| Approvals per | UL 1059 |
|---------------|---------|

Connection data

| | |
|-----------------------|---------------------------------|
| Connection technology | PUSH WIRE® |
| Strip length | 8 ... 9 mm / 0.31 ... 0.35 inch |
| Pole No. | 5 |

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG
 /Representative Office Romania
 Sos. Pipera-Tunari nr. 1/1
 building 1, 2nd floor | 077190 Voluntari, Ilfov
 Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?
 Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.

| | |
|-----------------------------------|----|
| Total number of connection points | 20 |
| Total number of potentials | 5 |
| Number of connection types | 1 |

Geometrical Data

| | |
|--------|----------------------|
| Width | 48,5 mm / 1.909 inch |
| Height | 15,3 mm / 0.602 inch |
| Depth | 24,5 mm / 0.965 inch |

Material Data


| | |
|-----------|----------|
| Fire load | 0,236 MJ |
| Weight | 15,8 g |

Commercial data

| | |
|-----------------------|--------------------------------|
| Product Group | 8 (Misc. Chassis Mount Blocks) |
| Packaging type | bag |
| Country of origin | DE |
| GTIN | 4044918437417 |
| Customs tariff number | 85369010000 |

Aprobări / certificate

Country specific Approvals

| Emblemă | Aprobare | Text de aprobare suplimentar | Nume certificat |
|--|---------------------------------|------------------------------|-----------------|
|  | CSA DEKRA Certification B.V. | C22.2 No. 158 | 70048844 |

Counterpart










Produse compatibile

tools

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG
/Representative Office Romania
Sos. Pipera-Tunari nr. 1/1
building 1, 2nd floor | 077190 Voluntari, Ilfov
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.

| | | |
|---|---|--|
|  | Nr. articol: 249-100 Operating tool; for terminal blocks with snap-in ground contact | www.wago.com/249-100 |
|  | Nr. articol: 271-120 Push-button; for retrofitting; loose | www.wago.com/271-120 |
| ferrule | | |
|  | Nr. articol: 209-151 Pin terminals; insulated; suitable for 271 and 272 Series; green | www.wago.com/209-151 |
|  | Nr. articol: 209-157 Pin terminals; insulated; suitable for 271 and 272 Series; blue | www.wago.com/209-157 |
|  | Nr. articol: 209-164 Pin terminals; insulated; suitable for 271 and 272 Series; natural | www.wago.com/209-164 |
| Marking accessories | | |
|  | Nr. articol: 210-110 Fiber-tip pen | www.wago.com/210-110 |
| assembling | | |
|  | Nr. articol: 271-702 Pins; for plate thickness 1 mm | www.wago.com/271-702 |
|  | Nr. articol: 271-711 Pins; for plate thickness 1 mm | www.wago.com/271-711 |
|  | Nr. articol: 271-712 Pins; for plate thickness 1.5 mm | www.wago.com/271-712 |

Descărcări

Documentation

Additional Information

| | | | |
|------------------------|-------------|---------------|------------|
| Technical explanations | Apr 3, 2019 | pdf 3,6 MB | Descărcare |
|------------------------|-------------|---------------|------------|

Installation Notes

Supus modificărilor.