

## Date

### Electrical data

### Ratings per IEC/EN 60664-1

Rated voltage (III/2)	400 V
Rated surge voltage (III/2)	4 kV
Rated current	18 A
Legend (ratings)	(III / 2) ≙ Overvoltage category III / Pollution degree 2

### Approvals per UL 1059

Approvals per	UL 1059
---------------	---------

### Connection data

Connection technology	PUSH WIRE®
Strip length	8 ... 9 mm / 0.31 ... 0.35 inch

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.

Pole No.	4
Total number of connection points	16
Total number of potentials	4
Number of connection types	1

### Geometrical Data

Width	38,5 mm / 1.516 inch
Height	19,5 mm / 0.767 inch
Depth	24,5 mm / 0.965 inch

### Material Data


Fire load	0,216 MJ
Weight	13,7 g

### Commercial data

Product Group	8 (Misc. Chassis Mount Blocks)
Packaging type	bag
GTIN	4044918430098

### Aprobări / certificate


#### Country specific Approvals

Emblemă	Aprobare	Text de aprobare suplimentar	Nume certificat
	CSA DEKRA Certification B.V.	C22.2 No. 158	70048844

### Counterpart

### Produse compatibile

#### tools

	Nr. articol: 249-100 Operating tool; for terminal blocks with snap-in ground contact	<a href="http://www.wago.com/249-100">www.wago.com/249-100</a>
--	---	--

Supus modificărilor.



Nr. articol: 271-120

Push-button; for retrofitting; loose

[www.wago.com/271-120](http://www.wago.com/271-120)

## Descărcări

### Documentation

#### Additional Information

Technical explanations

Apr 3, 2019

pdf  
3,6 MB

Descărcare

## Installation Notes

Supus modificărilor.