

**Date**

**Electrical data**

**Ratings per IEC/EN 60664-1**

Rated voltage (III/2)	400 V
Rated surge voltage (III/2)	4 kV
Rated current	18 A
Legend (ratings)	(III / 2) ≙ Overvoltage category III / Pollution degree 2

**Approvals per UL 1059**

Approvals per	UL 1059
---------------	---------

**Connection data**

Connection technology	PUSH WIRE®
Strip length	8 ... 9 mm / 0.31 ... 0.35 inch
Pole No.	5

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
 /Representative Office Romania  
 Sos. Pipera-Tunari nr. 1/1  
 building 1, 2nd floor | 077190 Voluntari, Ilfov  
 Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
 Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.

Total number of connection points	20
Total number of potentials	5
Number of connection types	1

### Geometrical Data

Width	48,5 mm / 1.909 inch
Height	15,3 mm / 0.602 inch
Depth	24,5 mm / 0.965 inch

### Material Data


Fire load	0,236 MJ
Weight	15,6 g

### Commercial data

Product Group	8 (Misc. Chassis Mount Blocks)
Packaging type	bag
Country of origin	DE
GTIN	4044918437332
Customs tariff number	85369010000

### Aprobări / certificate

#### Country specific Approvals

Emblemă	Aprobare	Text de aprobare suplimentar	Nume certificat
	CSA DEKRA Certification B.V.	C22.2 No. 158	70048844

### Counterpart

### Produse compatibile

### Marking accessories

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.



Nr. articol: 210-110  
Fiber-tip pen

[www.wago.com/210-110](http://www.wago.com/210-110)

#### tools



Nr. articol: 271-120  
Push-button; for retrofitting; loose

[www.wago.com/271-120](http://www.wago.com/271-120)

#### assembling



Nr. articol: 271-702  
Pins; for plate thickness 1 mm

[www.wago.com/271-702](http://www.wago.com/271-702)



Nr. articol: 271-711  
Pins; for plate thickness 1 mm

[www.wago.com/271-711](http://www.wago.com/271-711)



Nr. articol: 271-712  
Pins; for plate thickness 1.5 mm

[www.wago.com/271-712](http://www.wago.com/271-712)

#### ferrule



Nr. articol: 209-151  
Pin terminals; insulated; suitable for 271 and 272 Series; green

[www.wago.com/209-151](http://www.wago.com/209-151)



Nr. articol: 209-157  
Pin terminals; insulated; suitable for 271 and 272 Series; blue

[www.wago.com/209-157](http://www.wago.com/209-157)



Nr. articol: 209-164  
Pin terminals; insulated; suitable for 271 and 272 Series; natural

[www.wago.com/209-164](http://www.wago.com/209-164)

## Descărcări

### Documentation

#### Additional Information

Technical explanations

Apr 3, 2019

pdf  
3,6 MB

Descărcare

## Installation Notes

Supus modificărilor.