



## Fișă tehnică | Număr articol: 774-9993/107-502

pre-assembled connecting cable; Eca; Socket/open-ended; 3-pole; Cod. A;  
H05VV-F 3G 2.5 mm<sup>2</sup>; 5 m; 2,50 mm<sup>2</sup>; white



[www.wago.com/774-9993/107-502](http://www.wago.com/774-9993/107-502)



### Descriere articol

- For round conduits and ducts
- 3- and 4-pole preassembled cables with 17.5 mm outer diameter for easy plug & play
- Plug-in integration into the electrical installation of hollow-wall boxes via adapter, for example

### Note:

Cables with a different fire class can be found in the eShop.

### Note on mismatching protection:

All WINSTA<sup>®</sup> components are 100% protected against mismatching when:

- a.) plugging different numbers of poles
- b.) plugging while incorrectly rotated
- c.) plugging while laterally staggered

### Date

#### Electrical data

Note on Contact Resistance

approx. 1 mΩ of contact resistance approx. 0.25 mΩ contact transition plug/socket

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.



## Ratings per IEC/EN 60664-1

|                             |   |
|-----------------------------|---|
| Ratings per                 | IEC/EN 60664-1  |
| Nominal voltage (III/3)     | 250 V   |
| Rated surge voltage (III/3) | 4 kV  |
| Rated current               | 20 A  |
| Legend (ratings)            | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

## Connection data

|                                 |                               |
|---------------------------------|-------------------------------|
| Pole No.                        | 3                             |
| Total number of potentials      | 3                             |
| Ground function                 | with preceding ground contact |
| Conductor preparation           | tip-bonded                    |
| Sheathed cable diameter         | 9,2 ... 11,4 mm               |
| Wire cross-section              | 2,5 mm <sup>2</sup>           |
| Strip length (outer insulation) | 55 mm                         |
| Connection type                 | Socket - Free end             |

## Geometrical Data

|              |     |
|--------------|-----|
| Total length | 5 m |
|--------------|-----|

## Mechanical data

|   |   |
|---|---|
| Mating force of a plug-in connection    | approx. 30 ... 70 N (depending on pole number)  |
| Retention force of a plug-in connection | when locked: > 80N  |
| Unmating force of a plug-in connection  | when unlocked: approx. 30 ... 70 N (depending on pole number)   |
| Number of mating cycles                 | 200, without resistive load<br>100, with resistive load $I_N = 20$ A, tested (2.5mm <sup>2</sup> /AWG 14) |

|                             |   |
|-----------------------------|---|
| Connection type             | Socket - Free end   |
| Type of pre-assembled cable | Connecting cable  |
| Cable type                  | H05VV-F 3G2.5   |
| Marking                     | L N   |
| Protection type             | IP20  |
| Note on protection type     | Only when mated (these compact connectors are not designed for use in open, easily accessible areas). |

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.



|             |                            |
|-------------|----------------------------|
| Application | General mains applications |
|-------------|----------------------------|

**Plug connection**

|                               |               |
|-------------------------------|---------------|
| Mismating protection          | Yes           |
| Locking of plug-in connection | locking lever |

**Material Data**

|                         |  |
|-------------------------|--|
| Color                   | white                                    |
| Insulation material     | Polyamide 66 (PA 66)                     |
| Fire class per EN 50575 | E <sub>ca</sub>                          |
| Contact material        | Copper or copper alloy (surface-treated) |
| Fire load               | 13,369 MJ                                |
| Connector color         | white                                    |
| Strain relief color     | white                                    |
| Sheath material         | PVC                                      |
| Weight                  | 806 g                                    |


**Environmental Requirements**

|  |   |
|--|---|
| Processing temperature                   | -5 ... +40 °C   |
| Continuous operating temperature         | -35 ... +85 °C  |
| Note on continuous operating temperature | PVC cable for temperatures ≤ 70 °C (including halogen-free)<br>Insulating parts for temperatures ≤ 105 °C |

**Commercial data**

|                       |               |
|-----------------------|---------------|
| Packaging type        | not packed    |
| Country of origin     | DE            |
| GTIN                  | 4045454322946 |
| Customs tariff number | 85444290900   |

**Aprobări / certificate****Country specific Approvals**

| Emblemă  | Aprobare                        | Text de aprobare suplimentar | Nume certificat |
|--|---------------------------------|------------------------------|-----------------|
|  | CCA<br>DEKRA Certification B.V. | -                            | NTR NL<br>6374  |

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.



KEMA/KEUR  
DEKRA Certification B.V.

-

2118353.01

## Counterpart

### Descărcări

#### CAD/CAE-Data

##### CAD data

2D/3D Models 774-9993/107-502

[URL](#)

[Descărcare](#)

##### CAE data

WSCAD Universe 774-9993/107-502

[URL](#)

[Descărcare](#)

## Installation Notes

### Familie de produse

**<i>WINSTA</i>® RD**

Afișare globală produse din familie.

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: [info-RO@wago.com](mailto:info-RO@wago.com)

Aveți întrebări despre produsele noastre?

Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.