

PRODUCT DATASHEETP CLAS A 150 21 W/2700K E27

PARATHOM CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Very long lifetime of up to 25,000 h
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

PRODUCT FEATURES

- LED alternative to conventional lamps
- Good quality of light; color rendering index R_a : ≥ 80 ; constant chromaticity
- High color consistency: < 6 SDCM
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Rated wattage	21.00 W
Nominal wattage	21.00 W
Nominal voltage	220240 V
Max. lamp no. on circuit break. 10 A (B)	45
Max. lamp no. on circuit break. 16 A (B)	72
Operating frequency	5060 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	150 W


Photometrical data

Nominal luminous flux	2452 lm
Rated luminous flux	2452 lm
Rated color temperature	2700 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	2452 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Color rendering index Ra	≥80

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	143.0 mm
----------------	----------

Diameter	67.0 mm
Outer bulb	A67
Length	143.0 mm

Temperatures & operating conditions

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E27		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Frosted		
Show WEEE picto	Yes		
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value		

Capabilities

Dimmable	Yes
----------	-----


Certificates & standards


Energy efficiency class	A+
Energy consumption	21 kWh/1000h

Country-specific categorizations

ILCOS	DRAA/F-21/827-220-240-E27-60
Order reference	LEDPCLA150D 21W


Light Distribution





LDC typ polar

LDC typ polar



LDC typ polar

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x	Gross weight	Volume
		height)		

4052899959217	Folding carton box 1	67 mm x 67 mm x 145 mm	184.00 g	0.65 dm³
4052899959668	Shipping carton box 10	348 mm x 145 mm x 159 mm	1967.00 g	8.02 dm ³
4058075147072	Folding carton box 1	67 mm x 67 mm x 145 mm	233.00 g	0.65 dm³
4058075147089	Shipping carton box 10	345 mm x 142 mm x 157 mm	1947.00 g	7.69 dm³
4058075292611	Folding carton box 1	67 mm x 67 mm x 145 mm	233.00 g	0.65 dm³
4058075292628	Shipping carton box 10	348 mm x 145 mm x 159 mm	2457.00 g	8.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For dimming conformity see

www.ledvance.com/dim

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.