

Date

Electrical data

Ratings per IEC/EN 60664-1

Legend (ratings)

(III / 3) ≙ Overvoltage category III / Pollution degree 3

Material Data

Color	light gray
Insulation material	Polyamide 66 (PA 66)
Fire load	10,62 MJ
Weight	1300 g

Environmental Requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG
/Representative Office Romania
Sos. Pipera-Tunari nr. 1/1
building 1, 2nd floor | 077190 Voluntari, Ilfov
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.

Note on continuous operating temperature

Insulating parts for temperatures $\leq 105\text{ }^{\circ}\text{C}$

Commercial data

Product Group	20 (WINSTA)
Packaging type	BOX
Country of origin	CH
GTIN	4045454006327
Customs tariff number	85444995000



Counterpart

Produse compatibile

tools

	Nr. articol: 897-952 Stripping knife; for flat cable 5 x 16 mm	www.wago.com/897-952
	Nr. articol: 897-970 Cutter	www.wago.com/897-970

protection

	Nr. articol: 897-1650 Flat cable end cover; 5-pole; for flat cable 16 mm ² ; Plastic; transparent	www.wago.com/897-1650
	Nr. articol: 897-901 Insulating tape for flat cable; 5-pole/3-pole; for flat cable 10 mm ² ; acid green	www.wago.com/897-901

Descărcări

Documentation

Additional Information

pdf Descărcare
530,5 kB

CAD/CAE-Data

CAE data

WSCAD Universe 897-1651	URL	Descărcare
-------------------------	-----	------------

Supus modificărilor.



Installation Notes

Familie de produse

<i>WINSTA</i>® IDC

Afișare globală produse din familie.

Supus modificărilor.