



Date

Connection data

Pole No.	4
----------	---

Mechanical data

Mounting type	Snap-in
Suitable	for cutout

Material Data

Color	black
Insulation material	Polyamide 66 (PA 66)
Flammability class per UL94	V0
Fire load	0,064 MJ
Weight	2,5 g

Environmental Requirements

Processing temperature	-5 ... +40 °C
------------------------	---------------

Supus modificărilor.



Continuous operating temperature

-35 ... +85 °C

Note on continuous operating temperature

Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (WINSTA)
Packaging type	BOX
Country of origin	DE
GTIN	4017332802147
Customs tariff number	39269097900

Counterpart

Descărcări

CAD/CAE-Data

CAD data

2D/3D Models 770-644	URL	Descărcare
----------------------	---------------------	----------------------------

CAE data

WSCAD Universe 770-644	URL	Descărcare
------------------------	---------------------	----------------------------

Installation Notes

Familie de produse

<i>WINSTA</i>® MIDI

Afișare globală produse din familie.

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG
/Representative Office Romania
Sos. Pipera-Tunari nr. 1/1
building 1, 2nd floor | 077190 Voluntari, Ilfov
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.