



## Date

### Connection data

Pole No.	3
----------	---

### Mechanical data

Mounting type	Snap-in
Suitable	for cutout

### Material Data

Color	white
Insulation material	Polyamide 66 (PA 66)
Flammability class per UL94	V0
Fire load	0,051 MJ
Weight	1,7 g

Supus modificărilor.



## Environmental Requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

## Commercial data

Product Group	20 (WINSTA)
Packaging type	BOX
Country of origin	DE
GTIN	4017332755450
Customs tariff number	39269097900

## Counterpart

### Descărcări

#### CAD/CAE-Data

##### CAD data

2D/3D Models 770-693	URL	Descărcare
----------------------	-----	------------

##### CAE data

WSCAD Universe 770-693	URL	Descărcare
------------------------	-----	------------

## Installation Notes

## Familie de produse

<i>WINSTA</i>® MIDI  
[Afișare globală produse din familie.](#)

Supus modificărilor.

WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.