


AGRIMAX RT 765

TIRE SIZE	580/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	180 D



DIMENSIONS IS STANDARD

SW (MM)	577	RIM REC	W 18 L
OD (MM)	1827	RIM ALT	DW 18 L; DD 18 L
SLR (MM)	821	ECE	E11-106R-005836
RC (MM)	5505	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	4.6
65	3180	3875	4930	5480	6000	6470	6930	7370	7790	8000
50	3340	4070	5180	5755	6300	6795	7280	7740	8180	8400
40	3485	4245	5400	6005	6570	7085	7590	8075	8535	8760
30	3660	4460	5670	6305	6900	7445	7970	8480	8960	9200
25	3770	4595	5845	6495	7110	7670	8215	8735	9235	9480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.