

# XL GRIP (L3)

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | 17.5 - 25                       |
| <b>UM</b>           | US STANDARD                     |
| <b>CONSTRUCTION</b> | BIAS                            |
| <b>MACHINERY</b>    | RADLADER / RADLADER / PLANIERER |
| <b>VERSION</b>      | STANDARD                        |
| <b>TIRE TYPE</b>    | TL                              |



## ABMESSUNGEN US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA-CODE</b> | 94015719 | <b>RIM REC</b>  | 14.00/1.5 |
| <b>OD (IN)</b>  | 53.0     | <b>PR</b>       | 16        |
| <b>SLR (IN)</b> | 24.5     | <b>TRA CODE</b> | E3/L3     |
| <b>RC (IN)</b>  | 156.7    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44   | 69    |
|-----------|------|-------|
| 30        | 9350 | -     |
| 5         | -    | 16100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.