

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>380/85 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	135 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94033096	<b>RC (IN)</b>	165.0
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	55.4	<b>RIM ALT</b>	W 11 ; W 13
<b>SLR (IN)</b>	24.9	<b>ECE</b>	E4-106R-000594

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	2650	3090	3520	3950	4380	4800
<b>25</b>	2650	3090	3520	3950	4380	4800
<b>20</b>	2830	3300	3760	4220	4680	5150
<b>5 LT</b>	3550	4130	4720	5290	5870	6450
<b>5 HT</b>	2830	3300	3760	4220	4680	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.