


# RIDEMAX IT 697 (M+S)

<b>TIRE SIZE</b>	<b>650/85 R 38 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 D ; 183 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	709	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	2071	<b>RIM ALT</b>	DW 20 B; DW 21 B
<b>SLR (MM)</b>	974	<b>ECE</b>	E11-106R-006761
<b>RC (MM)</b>	6280	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
65	3525	4350	5100	5925	6675	7500
50	3805	4700	5510	6400	7210	8100
40	4115	5075	5950	6915	7790	8750
30	4230	5220	6120	7110	8010	9000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.