

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>580/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	577	<b>RIM REC</b>	W 18 L
<b>OD (MM)</b>	1827	<b>ECE</b>	E11-106R-005526
<b>SLR (MM)</b>	821	<b>SRI</b>	875
<b>RC (MM)</b>	5471	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	2135	2480	2830	3180	3530	3875
50	2240	2605	2975	3340	3705	4070
40	2335	2720	3100	3485	3865	4245
30	2455	2855	3260	3660	4060	4460
10 LT	2860	3325	3795	4260	4730	5195
10 HT	2455	2855	3260	3660	4060	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.