

# FLOTATION 648

<b>TIRE SIZE</b>	<b>650/65 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	167 A8/163 B
<b>LI/SS FREE ROLLING</b>	179 A8/175 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94030149	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	26.4	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	65.4	<b>ECE</b>	E11-106R-004562
<b>SLR (IN)</b>	28.0	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
<b>5 FR</b>	21260	22620	23920
<b>10 FR</b>	19140	20360	21530
<b>20 FR</b>	17010	18100	19140
<b>25 FR</b>	15190	16160	17080
<b>30 FR</b>	13670	14540	15210
<b>5 DW</b>	14960	15910	16820
<b>10 DW</b>	13460	14320	15130
<b>20 DW</b>	11960	12730	13460
<b>25 DW</b>	10680	11360	12010
<b>30 DW</b>	9610	10230	10750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.