


AGRIMAX V- FLECTO

TIRE SIZE	VF 600/70 R 28 NRO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	167 D



DIMENSIONI IS STANDARD

SW (MM)	603	RIM REC	DW 21 B
OD (MM)	1551	RIM ALT	DW 20 B
SLR (MM)	662	ECE	E11-106R-008814
RC (MM)	4596	SRI	725

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2425	2820	3270	3665	4060	4455	4955
FROM 65 TO 40	2670	3105	3595	4030	4465	4905	5450
30	2720	3165	3665	4110	4555	4995	5555
20	2775	3225	3735	4190	4645	5095	5665
10	2935	3415	3955	4435	4915	5395	5995
*UPTO 10 CYC WITH FRONT LOADER	3735	4345	5035	5645	6255	6865	7630
10 HT	2720	3165	3665	4110	4555	4995	5555

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.