


# RIDEMAX FL 615

<b>TIRE SIZE</b>	<b>VF 800/65 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	REMORQUE / VÉHICULE CITERNE / ÉPANDEUR / OUTILLAGE AGRICOLE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	190 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94513925	<b>RC (IN)</b>	220.9
<b>SW (IN)</b>	32.1	<b>RIM REC</b>	DW 28 B
<b>OD (IN)</b>	72.8	<b>RIM ALT</b>	DW 27 B
<b>SLR (IN)</b>	31.9	<b>ECE</b>	E11-106R-0010408

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41
40	11450	12850	15660	17770	20570	23370
30	13400	15050	18330	20790	24070	27350
25	14780	16590	20200	22920	26530	30150
20	16160	18130	22090	25050	29010	32960
15	16730	18770	22870	25940	30040	34130
10	17420	19540	23810	27010	31270	35530
5	18780	21090	25680	29130	33730	38330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.