

AS 504

TIRE SIZE	7.5L - 15
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	100 A8
LI/SS FREE ROLLING	113 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	210	RIM REC	6 LB
OD (MM)	765	RIM ALT	5 K; 5½ J; 5½ K
SLR (MM)	354	ECE	E4-106R-002632
RC (MM)	2280	PR	8

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	1610
25 FR	1370
30 FR	1290
40 FR	1150
10 DW	1120
25 DW	950
30 DW	895
40 DW	800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.