


# MULTIMAX MP 525

<b>TIRE SIZE</b>	<b>405/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ГРЕЙДЕР
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	152 J; 168 A2



## РАЗМЕРЫ IS STANDARD

<b>OD (MM)</b>	1076	<b>RIM ALT</b>	12; 13 SDC
<b>SLR (MM)</b>	482	<b>ECE</b>	E11-54R-0020576
<b>RC (MM)</b>	3260		
<b>RIM REC</b>	13		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	6.00
100	3550
10	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.