

# TR 315

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>31X15.50 - 15</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | ARBETSFORDON / SKÖRDEMASKIN<br>FÖR FRUKTODLING /<br>DIKNINGSMASKIN / SKÖRDEMASKIN /<br>ARBETSFORDON |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 390  | <b>RIM REC</b> | 13 LB          |
| <b>OD (MM)</b>  | 800  | <b>ECE</b>     | E4-106R-002208 |
| <b>SLR (MM)</b> | 354  | <b>PR</b>      | 8              |
| <b>RC (MM)</b>  | 2320 |                |                |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.10</b> |
| 50                | 1250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.