


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>440/65 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	138 D ; 141 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94042753	<b>RC (IN)</b>	127.6
<b>SW (IN)</b>	17.4	<b>RIM REC</b>	W 14 L
<b>OD (IN)</b>	42.5	<b>RIM ALT</b>	W 13 ; W 15 L
<b>SLR (IN)</b>	18.9	<b>ECE</b>	E4-106R-000760

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2450	2870	3280	3650	4010	4320	4790	5200
30	2580	3010	3450	3840	4210	4540	5040	5470
25	2680	3130	3580	3980	4380	4720	5220	5680
20	2820	3300	3780	4200	4620	4970	5510	5990
5 LT	3280	3850	4400	4890	5380	5800	6430	6980
5 HT	2820	3300	3780	4200	4620	4970	5510	5990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.