

# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/40 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	160 A8/156 B
<b>LI/SS FREE ROLLING</b>	173 A8/169 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	700	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1170	<b>ECE</b>	E4-106R-002281
<b>SLR (MM)</b>	510	<b>PR</b>	18
<b>RC (MM)</b>	3537		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80	3.00	3.20
10 FR	8415	8765	9100
20 FR	7575	7890	8190
30 FR	6730	7010	7280
40 FR	6010	6260	6500
50 FR	5410	5635	5800
10 DW	5825	6070	6300
20 DW	5240	5460	5670
30 DW	4660	4855	5040
40 DW	4160	4335	4500
50 DW	3745	3900	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.