


# AS 504

<b>TIRE SIZE</b>	<b>16.5/85 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	155 A8
<b>LI/SS FREE ROLLING</b>	168 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94019113	<b>RC (IN)</b>	158.0
<b>SW (IN)</b>	16.3	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	52.2	<b>RIM ALT</b>	W 14 L; W 15 L
<b>SLR (IN)</b>	23.0	<b>ECE</b>	E4-106R-001877

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>55</b>
<b>5 FR</b>	17280
<b>15 FR</b>	14690
<b>20 FR</b>	13820
<b>25 FR</b>	12350
<b>5 DW</b>	11960
<b>15 DW</b>	10160
<b>20 DW</b>	9570
<b>25 DW</b>	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.