


AGRIMAX V- FLECTO

| | |
|--------------|--|
| TIRE SIZE | VF 650/65 R 34 NRO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR DE ALTA POTENCIA / TRACTOR |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 170 D |



DIMENSIONES IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 650 | RIM REC | DW 23 B |
| OD (MM) | 1710 | RIM ALT | DW 21 B |
| SLR (MM) | 756 | ECE | E11-106R-008812 |
| RC (MM) | 5110 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|------|------|------|------|------|
| 70 | 2780 | 3220 | 3655 | 4145 | 4530 | 5075 | 5460 |
| FROM 65 TO 40 | 3060 | 3540 | 4020 | 4560 | 4980 | 5580 | 6000 |
| 30 | 3120 | 3610 | 4100 | 4650 | 5075 | 5690 | 6120 |
| 20 | 3180 | 3680 | 4180 | 4740 | 5175 | 5800 | 6240 |
| 10 | 3365 | 3890 | 4420 | 5015 | 5475 | 6135 | 6600 |
| *UPTO 10 CYC WITH FRONT LOADER | 4280 | 4955 | 5625 | 6380 | 6970 | 7810 | 8400 |
| 10 HT | 3120 | 3610 | 4100 | 4650 | 5075 | 5690 | 6120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.