


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 650/60 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	660	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1676	<b>RIM ALT</b>	DW21B
<b>SLR (MM)</b>	750	<b>ECE</b>	E11-106R-007210
<b>RC (MM)</b>	4996	<b>SRI</b>	775

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2605	3010	3420	3880	4235	4590	5100
<b>FROM 65 TO 40</b>	2860	3305	3755	4260	4650	5040	5600
30	2915	3375	3830	4345	4745	5145	5715
20	2975	3375	3830	4345	4745	5145	5715
10	3145	3635	4130	4685	5115	5545	6160
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	4000	4630	5255	5960	6510	7060	7840
10 HT	2915	3375	3830	4345	4745	5145	5715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.