


AS 504

TIRE SIZE	10.0/75 - 15.3
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	INDUSTRIAL
TIRE TYPE	TL
LI/SS DRIVE WHEEL	106 A8
LI/SS FREE ROLLING	119 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019441	RC (IN)	94.6
SW (IN)	10.4	RIM REC	9.00
OD (IN)	30.9	PR	8
SLR (IN)	14.2		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	4200
15 FR	3570
20 FR	3360
25 FR	3000
5 DW	2930
15 DW	2490
20 DW	2350
25 DW	2090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.