

EARTHMAX SR 34



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 34

EARTHMAX SR 34 is an All Steel radial tyre specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its also contributes to an extended tyre life-cycle even under the most heavy-duty service condition



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	16.00 R 25	TL	E3+	***	183 B	11.25/2.0	-	190	440	1508	693	4575	36	CR
	16.00 R 25	TL	E3+	**	177 B	11.25/2.0	-	190	440	1508	693	4575	36	CR
	16.00 R 25	TL	E3+	***	183 B	11.25/2.0	-	0	440	1508	693	4575	36	UCRC

CR: CUT RESISTANT COMPOUND, UCRC: ULTRA CUT RESISTANT COMPOUND

TECHNOLOGIES					PERFORMANCES			
								
								

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES
  E3+  B 183 kg	   	   

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026