

AS 504

TIRE SIZE	19.0/45 - 17
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	134 A8
LI/SS FREE ROLLING	147 A8



РАЗМЕРЫ US STANDARD

USA CODE	94064465	RC (IN)	101.5
SW (IN)	18.3	RIM REC	16.00
OD (IN)	34.1	ECE	E11-106R-006179
SLR (IN)	15.3	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	9520
15 FR	8090
20 FR	7615
25 FR	6800
5 DW	6550
15 DW	5570
20 DW	5240
25 DW	4680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.