


TR 315

| | |
|---------------------|---|
| TIRE SIZE | 23X10.50 - 12 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / МАШИНА ДЛЯ СБОРА ФРУКТОВ / ТРАНШЕЙНЫЙ ЭКСКАВАТОР / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 255 | RIM REC | 8½ JA |
| OD (MM) | 600 | RIM ALT | 7 JA |
| SLR (MM) | 272 | ECE | E4-106R-002179 |
| RC (MM) | 1840 | PR | 4 |

LOAD CAPACITY (KG/TIRE)

| | |
|-------------------|-------------|
| KM/H / BAR | 1.40 |
| 15 | 600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.