


# AW 711

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>380/55 R 16.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL       |
| <b>MACHINERY</b>    | ERNTMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE /<br>ERNTMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>      | STUBBLE RESISTANT  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 150 A8/B   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA-CODE</b> | 94044757 | <b>RC (IN)</b> | 98.4           |
| <b>SW (IN)</b>  | 14.2     | <b>RIM REC</b> | 12             |
| <b>OD (IN)</b>  | 32.7     | <b>RIM ALT</b> | 11.75          |
| <b>SLR (IN)</b> | 14.6     | <b>ECE</b>     | E4-106R-001393 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 73    |
|-----------|------|------|------|------|------|------|------|------|------|-------|
| 30        | 2220 | 2890 | 3550 | 4070 | 4730 | 5400 | 5760 | 6360 | 6940 | 7400  |
| 25        | 2220 | 2890 | 3550 | 4070 | 4730 | 5400 | 5760 | 6360 | 6940 | 7400  |
| 20        | 2490 | 3230 | 3980 | 4560 | 5300 | 6050 | 6460 | 7120 | 7780 | 8280  |
| 15        | 2650 | 3440 | 4230 | 4840 | 5630 | 6430 | 6870 | 7570 | 8280 | 8800  |
| 10        | 2800 | 3640 | 4480 | 5130 | 5960 | 6800 | 7270 | 8010 | 8760 | 9310  |
| 5         | 3110 | 4030 | 4970 | 5690 | 6620 | 7550 | 8070 | 8900 | 9720 | 10340 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.