

# RT 747 AGRO INDUSTRIAL

<b>TIRE SIZE</b>	<b>11L R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PALA COMPATTA / SOLLEVATORE TELESCOPICO / PALA COMPATTA / SOLLEVATORE TELESCOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	122 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94062737	<b>RC (IN)</b>	98.3
<b>SW (IN)</b>	11.4	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	33.5	<b>RIM ALT</b>	W 10 L
<b>SLR (IN)</b>	14.6	<b>ECE</b>	E11-106R-005769

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	32	35	38
5	2790	3370	3950	4230	4530	4850
15	2070	2570	3050	3310	3550	---
25	1940	2390	2850	3080	3310	---

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.