


# AGRIMAX RT 855

	<b>280/85 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	122 A8/B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	292	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	984	<b>RIM ALT</b>	W 9
<b>SLR (MM)</b>	447	<b>ECE</b>	E11-106R-007936
<b>RC (MM)</b>	2977	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	615	720	825	930	1035	1125	1335	1500
40	615	720	825	930	1035	1125	1335	1500
30	660	775	885	1000	1110	1205	1430	1605
10 LT	825	965	1110	1250	1390	1510	1790	2010
10 HT	660	775	885	1000	1110	1205	1430	1605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.