



## DATA SHEET

Dernière mise à  
jour  
10-07-2026

# TR 135

|                  |                     |
|------------------|---------------------|
| <b>TIRE SIZE</b> | <b>20.8 - 38</b>    |
| <b>UM</b>        | US STANDARD         |
| <b>MACHINERY</b> | TRACTEUR / REMORQUE |
| <b>VERSION</b>   | DUAL BEAD HD        |
| <b>TIRE TYPE</b> | TL                  |
| <b>LI/SS</b>     | 162 A8              |



### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94058778 | <b>RC (IN)</b> | 223.8           |
| <b>SW (IN)</b>  | 20.9     | <b>RIM REC</b> | W 18 L          |
| <b>OD (IN)</b>  | 72.2     | <b>RIM ALT</b> | W 16 L          |
| <b>SLR (IN)</b> | 33.3     | <b>ECE</b>     | E11-106R-004466 |

### LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>46</b> |
|------------------|-----------|
| 25               | 10470     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.