


RIDEMAX FL 615

| | |
|---------------------|--|
| TIRE SIZE | VF 900/65 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | REMORQUE / VÉHICULE CITERNE / ÉPANDÉUR / OUTILLAGE AGRICOLE |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 200 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| CODE USA | 94515349 | RC (IN) | 253.7 |
| SW (IN) | 35.1 | RIM REC | DW 30 B |
| OD (IN) | 83.3 | ECE | E11-106R-0011504 |
| SLR (IN) | 36.6 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 |
|-----------|-------|-------|-------|-------|-------|-------|
| 40 | 15120 | 16970 | 20680 | 23460 | 27160 | 30860 |
| 30 | 17700 | 19860 | 24190 | 27450 | 31780 | 36110 |
| 25 | 19510 | 21900 | 26690 | 30270 | 35040 | 39810 |
| 20 | 21330 | 23940 | 29170 | 33080 | 38300 | 43520 |
| 15 | 22090 | 24790 | 30190 | 34250 | 39660 | 45060 |
| 10 | 22990 | 25800 | 31440 | 35660 | 41290 | 46910 |
| 5 | 24810 | 27840 | 33920 | 38470 | 44540 | 50620 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.