


AGRIMAX V- FLECTO

TIRE SIZE	VF 480/70 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	153 D



РАЗМЕРЫ IS STANDARD

SW (MM)	495	RIM REC	W 18 L
OD (MM)	1430	RIM ALT	W 16 L; DW 18 L
SLR (MM)	645	ECE	E11-106R-0010762
RC (MM)	4353	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	1825	2120	2420	2720	3020	3320
FROM 65 TO 40	2005	2335	2660	2990	3320	3650
30	2045	2380	2715	3050	3385	3720
20	2085	2425	2770	3110	3450	3795
10	2205	2565	2930	3290	3650	4015
*UPTO 10 CYC WITH FRONT LOADER	2810	3270	3730	4190	4650	5110
10HT	2045	2380	2715	3050	3385	3720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.