


FL 630 ULTRA

| | |
|---------------------|--|
| TIRE SIZE | 560/60 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPREADER / TANKER / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 161 D ; 172 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------------|
| SW (MM) | 543 | RIM REC | AG 16.00 |
| OD (MM) | 1244 | RIM ALT | 16.00; 17.00; AG 20.00 |
| SLR (MM) | 535 | ECE | E11-106R-003013 |
| RC (MM) | 3760 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1350 | 1540 | 1730 | 2150 | 2445 | 2825 | 3200 | 3495 | 3835 | 4210 |
| 65 | 1480 | 1690 | 1900 | 2360 | 2685 | 3100 | 3515 | 3840 | 4210 | 4625 |
| 50 | 1795 | 2050 | 2300 | 2860 | 3250 | 3755 | 4260 | 4650 | 5100 | 5600 |
| 40 | 2020 | 2305 | 2585 | 3215 | 3655 | 4225 | 4790 | 5230 | 5735 | 6300 |
| 30 | 2240 | 2555 | 2865 | 3565 | 4055 | 4680 | 5310 | 5800 | 6360 | 6985 |
| 25 | 2340 | 2670 | 3000 | 3730 | 4240 | 4900 | 5560 | 6070 | 6655 | 7310 |
| 10 | 2665 | 3040 | 3415 | 4250 | 4830 | 5580 | 6330 | 6910 | 7580 | 8325 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.