

# AW 702

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>10.5/65 - 16</b>  |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | ❖ BIAS   |
| <b>MACHINERY</b>          | ПРЕСС-ПОДБОРЩИК /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / ПРИЦЕП /<br>КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / ПРИЦЕП |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 123 A8   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94009237 | <b>RC (IN)</b> | 91.7            |
| <b>SW (IN)</b>  | 10.6     | <b>RIM REC</b> | W 9             |
| <b>OD (IN)</b>  | 29.9     | <b>RIM ALT</b> | W 8; W 8 L      |
| <b>SLR (IN)</b> | 13.8     | <b>ECE</b>     | E11-106R-003513 |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>55</b> |
|------------------|-----------|
| 5 FR             | 4780      |
| 15 FR            | 4070      |
| 20 FR            | 3820      |
| 25 FR            | 3420      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.