


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>540/80 R 42 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D ; 173 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94062409	<b>RC (IN)</b>	231.3
<b>SW (IN)</b>	22.0	<b>RIM REC</b>	W 18 L
<b>OD (IN)</b>	76.0	<b>RIM ALT</b>	W 16 L
<b>SLR (IN)</b>	34.6	<b>ECE</b>	E11-106R-005714

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	5800	7160	8400	9750	10990	12350
30	6270	7740	9070	10540	11870	13340
25	6730	8310	9740	11320	12750	14330
20	8080	9980	11690	13580	15300	17200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.