

MP 567

| | |
|---------------------------|--|
| TIRE SIZE | 10.0/75 - 15.3 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊗ BIAS |
| MACHINERY | MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO / VEHÍCULO UNIVERSAL |
| VERSIÓN | IMPLEMENT |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 118 A8 |
| LI/SS FREE ROLLING | 130 A8 |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 258 | RIM REC | 9.0 |
| OD (MM) | 774 | ECE | E11-106R-003528 |
| SLR (MM) | 365 | PR | 14 |
| RC (MM) | 2401 | | |

LOAD CAPACITY (KG/TIRE)

| | |
|-------------------|-------------|
| KM/H / BAR | 5.50 |
| 40 FR | 1900 |
| 40 DW | 1320 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.