

MULTIMAX MP 513

| | |
|---------------------|--|
| TIRE SIZE | 365/70 R 18 MPT |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VEICOLO UNIVERSALE / AUTOCARRO PER FERTILIZZANTI / VEICOLO UNIVERSALE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 133 G |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|--------------------|
| CODICE USA | 94051366 | RC (IN) | 116.3 |
| SW (IN) | 14.2 | RIM REC | 11 |
| OD (IN) | 38.1 | RIM ALT | 11 SDC; 12; 12 SDC |
| SLR (IN) | 17.6 | ECE | E11-54R-0016138 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 36 | 44 | 51 | 54 |
|-----------|------|------|------|------|------|------|
| 55 | 2380 | 2820 | 3350 | 3880 | 4410 | 4540 |
| 40 | 2580 | 3040 | 3640 | 4210 | 4780 | 4940 |
| 25 | 2760 | 3240 | 3860 | 4450 | 5070 | 5220 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.