


AGRIMAX FORTIS

| | |
|--------------|--|
| TIRE SIZE | 710/75 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D ; 172 E |



DIMENSIONS IS STANDARD

| | | | |
|----------|------|---------|----------------|
| SW (MM) | 716 | RIM REC | DW 23 B |
| OD (MM) | 2133 | RIM ALT | DW 25 B |
| SLR (MM) | 970 | ECE | E4-106R-001835 |
| RC (MM) | 6406 | SRI | 1000 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 70 | 3025 | 3530 | 3970 | 4410 | 4855 | 5230 | 5800 | 6300 |
| 65 | 3315 | 3865 | 4350 | 4830 | 5315 | 5730 | 6350 | 6900 |
| 50 | 3480 | 4060 | 4565 | 5075 | 5580 | 6015 | 6670 | 7245 |
| 40 | 3630 | 4235 | 4765 | 5295 | 5825 | 6275 | 6960 | 7560 |
| 30 | 3810 | 4445 | 5000 | 5555 | 6110 | 6590 | 7305 | 7935 |
| 10 LT | 4440 | 5180 | 5830 | 6475 | 7125 | 7680 | 8510 | 9250 |
| 10 HT | 3810 | 4445 | 5000 | 5555 | 6110 | 6590 | 7305 | 7935 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.