

FL 637

520/50 R 17**UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** YAYICI / TANKER / RÖMORK /
UYGULAMALI MAKINE**VERSION** STANDARD**TIRE TYPE** TL

151 D ; 148 E



UNDEFINED IS STANDARD

SW (MM)	516	RIM REC	16.00
OD (MM)	952	ECE	E11-106R-004070
SLR (MM)	414	SRI	450
RC (MM)	2930		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
70	915	1170	1420	1610	1860	2115	2335	2555	2805	3150
65	1005	1280	1555	1760	2040	2315	2555	2795	3075	3450
50	1215	1545	1880	2130	2465	2800	3090	3385	3720	4175
40	1365	1740	2115	2395	2775	3150	3475	3805	4180	4695
30	1515	1930	2345	2660	3075	3495	3860	4225	4640	5210
25	1585	2020	2455	2785	3220	3655	4040	4420	4855	5455
10	1805	2300	2795	3170	3665	4165	4600	5035	5530	6210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.