


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94058617	<b>RC (IN)</b>	240.3
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	79.5	<b>RIM ALT</b>	DW 25 B
<b>SLR (IN)</b>	36.0	<b>ECE</b>	E11-106R-004896

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
<b>30</b>	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
<b>25</b>	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
<b>20</b>	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690
<b>5 LT</b>	8200	9530	10860	12410	13750	15070	16620	17500	19280	20830	22160
<b>5 HT</b>	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.